

LUKOIL GARDEN 2T

2-stroke small engine oil for garden equipment

MEETS REQUIREMENTS

API TC
JASO FB
ISO E-GB

PRODUCT DESCRIPTION

LUKOIL GARDEN 2T – modern high-quality mineral oil, designed as a component of fuel-oil mixture for 2-Stroke gasoline small engines of garden equipment.

LUKOIL GARDEN 2T is formulated with high-quality base stocks and highly effective advanced ashless additive package. **LUKOIL GARDEN 2T** provides excellent detergent, antiwear and lubricating properties. Low quantity of ash significantly decreases risk of sludge and deposits formation on inner surfaces of the engine, provides prolonged life of spark plugs and the risk of surface ignition and makes the oil smokeless and safe for the environment.

Due to the thoroughly selected formulation, **LUKOIL GARDEN 2T** provides highly-effective antiwear protection of an engine even under severe operating conditions and extends the lifetime of your garden equipment.

APPLICATION

LUKOIL GARDEN 2T is recommended for using in modern 2-Stroke engines of garden equipment: lawn mowers, chain saws, cultivators and tillers. **LUKOIL GARDEN 2T** is recommended for Husqvarna, Stihl, Honda, Huter and other garden equipment.

Proportion of the mixing must meet to the maintenance manual. Usually it is fuel:oil = 50:1

The product name in an order:
 Motor oil LUKOIL GARDEN 2T, STO 79345251-095-2016

TYPICAL TEST DATA

PROPERTY	Test method	LUKOIL GARDEN 2T
Kinematic viscosity at 100 °C, mm ² /s	ASTM D445	14.3
Viscosity Index	ASTM D2270	93
Pour Point, °C, °C	GOST 20287 B	-16
Total base number, mg KOH/1 g oil	ASTM D2896	0.9
Sulphated ash, %	ASTM D874	0.1

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO "LLK-International".