

# LUKOIL MOTO 4T

## SAE 5W-40, 10W-30, 10W-40

4-Stroke small engine oil

### APPROVALS

**JASO** MA2 (SAE 10W-30)  
**HUTER**

### MEETS REQUIREMENTS

**API** SL  
**JASO** MA2 (SAE 5W-40, 10W-40)

### PRODUCT DESCRIPTION

**LUKOIL MOTO 4T SAE 5W-40, 10W-30, 10W-40** – modern high-quality semi-synthetic multigrade premium oils, designed for 4-Stroke gasoline engines of motor-cycles, mopeds, scooters and snowmobiles.

The oils provide highly-effective protection of the engine, perfect transmission operation and optimum clutch performance, has excellent detergent and antioxidant performance, improved antiwear, anticorrosion and antifoam properties, demonstrated incredible results when operating under low temperatures and as well as high friction performance, which guarantees excellent clutch performance even under the most severe conditions of operation.

**LUKOIL MOTO 4T SAE 5W-40, 10W-30, 10W-40** are formulated with high-quality base stocks, synthetic components and highly-effective advanced additives package of one of the best additive manufactures in the world, which provides perfect protection of the engine and transmission even under severe operating conditions and extends the lifetime of your transportation.

**LUKOIL MOTO 4T SAE 5W-40, 10W-30, 10W-40** oils meet or exceed the requirements of all Japanese and American motorcycles manufacturers.

### APPLICATION

The oils are recommended for using in modern 4-Stroke engines of motorcycles, mopeds, scooters and snowmobiles. The oils are intended for use in transmissions and clutches of modern motorcycles when they require lubrication by motor oil.

The product name in an order:

Motor oil LUKOIL MOTO 4T SAE 5W-40, STO 79345251-061-2014  
 Motor oil LUKOIL MOTO 4T SAE 10W-30, STO 79345251-061-2014  
 Motor oil LUKOIL MOTO 4T SAE 10W-40, STO 79345251-061-2014

### TYPICAL TEST DATA

PROPERTY	Test method	LUKOIL MOTO 4T		
		5W-40	10W-30	10W-40
Viscosity Grade SAE		5W-40	10W-30	10W-40
Density at 20°C, kg/m <sup>3</sup>	ASTM D4052 / GOST 3900	856.1	867.6	866.8
Kinematic viscosity at 100 °C, mm <sup>2</sup> /s	ASTM D445 / GOST 33	13.65	12.1	12.6
Viscosity Index	ASTM D2270 / GOST 25371	160	156	150
Noack evaporation loss, %	ASTM D92 / GOST 4333	224	224	232
Pour Point, °C	GOST 20287 B	-42	-35	-32
Total Base Number, mg KOH/1 g oil	ASTM D2896 / GOST 30050	7.2	7.0	7.1
Sulphated ash, %	ASTM D874 / GOST 12417	0.8	1.1	0.8

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO "LLK-International".