

LUKOIL OUTBOARD 4T SAE 10W-40

Motor oil for 4-Stroke engines of watercrafts

MEETS REQUIREMENTS

NMMA FC-W
API SL

PRODUCT DESCRIPTION

LUKOIL OUTBOARD 4T SAE 10W-40 is a modern high-quality semi-synthetic motor oil for 4-Stroke gasoline engines of launches, yachts, jet skis and motor boats.

The oil is manufactured on high-quality base oil using synthetic component and thoroughly balanced high-efficiency additive package. The product having effective lubricating, detergency, anti-wear properties and improved anticorrosion properties provides reliable engine protection under any, even the severest

operating conditions, thus prolonging lifetime of your engine.

APPLICATION

LUKOIL OUTBOARD 4T SAE 10W-40 is recommended for modern 4-Stroke highly accelerated outboard and water-jet motors with water and air cooling of launches, yachts, jet skis, motor boats and any other engines, which require NMMA (National Marine Manufacturing Association) FC-W lubricants. **LUKOIL OUTBOARD 4T SAE 10W-40** is recommended for Mercury, Suzuki, Yamaha, Tohatsu, Honda, Bombardier and other enined.

The product name in an order:

Motor oil LUKOIL OUTBOARD 4T SAE 10W-40, STO 79345251-094-2016

TYPICAL TEST DATA

PROPERTY	Test method	LUKOIL OUTBOARD 4T SAE 10W-40
Density at 20 °C, kg/m ³	ASTM D4052 / GOST 3900	864
Kinematic viscosity at 100 °C, mm ² /s	ASTM D445 / GOST 33 / GOST R 53708	13.53
Viscosity index	ASTM D2270 / GOST 25371	155
Sukphated ash, %	ASTM D874 / GOST 12417	0.9
Total base number, mg KOH/1 g oil	GOST 30050 / ASTM D2896	6.2
Flash point (COC), °C	ASTM D92 / GOST 4333	230
Pour point, °C	GOST 20287 B	-37
Noack evaporation loss, %	ASTM D5800 / DIN 51581-1	9.5

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO "LLK-International".