

# LUKOIL LUXE synthetic SAE 5W-40, API SN/CF

Fully synthetic multi-grade engine oil

## APPROVALS

**API SN** - licensed (API №2523)  
**MB-Approval** 229.5  
**Renault** RN 0700 / 0710  
**JSC «AVTOVAZ»**  
**VW** 502 00 / 505 00

## MEETS REQUIREMENTS

**API CF**  
**ACEA** A3/B4  
**PSA** B71 2296  
**FIAT** 9.55535-N2, 9.55535-Z2

## PRODUCT DESCRIPTION

**LUKOIL LUXE synthetic SAE 5W-40, API SN/CF** is fully synthetic multi-grade engine oil meeting requirements of API SN/CF, ACEA A3/B4. The product was formulated using high-quality synthetic base oils with involvement of advanced technology additives.

## APPLICATION

**LUKOIL LUXE synthetic SAE 5W-40, API SN/CF** is designed for gasoline and diesel engines (without DPF), including turbocharged ones, of modern passenger cars.

## BENEFITS

- Improved low-temperature properties insure reliable engine protection at severe winter conditions
- Prevents high and low temperature deposits on engine components
- Provides excellent engine protection against wear
- Adapted for start-stop mode of severe conditions of urban cycle

The product name in an order:

LUKOIL LUXE Synthetic Multigrade Engine Oil SAE 5W-40, API SN/CF, STO 00044434-003-2005

## TYPICAL TEST DATA

PROPERTY	Test method	LUKOIL LUXE synthetic SAE 5W-40, API SN/CF
Density at 15°C, kg/m <sup>3</sup>	ASTM D1298 / GOST R 51069 / ASTM D4052	848.1
Kinematic viscosity at 100 °C, mm <sup>2</sup> /s	ASTM D445 / GOST 33 / GOST R 53708	13.6
Viscosity Index	ASTM D2270 / GOST 25371	176
Apparent viscosity CCS at -30 °C, mPa·s	ASTM D5293 / GOST 52559	4,942
Apparent viscosity MRV at -35 °C, mPa·s	ASTM D4684 / GOST 52257	29,300
Total base number, mg KOH/1 g oil	GOST 11362	8.5
Total base number, mg KOH/1 g oil	ASTM D2896 / GOST 30050	9.8
Sulphated ash, %	GOST 12417 / ASTM D874	0.96
Noack evaporation loss, %	ASTM D5800	10
Flash Point, COC, °C	GOST 4333 / ASTM D92	235
Pour Point, °C	GOST 20287 B	-40

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO "LLK-International".