

LUKOIL LUXE SAE 20W-50, API SL/CF

High quality mineral engine oil

MEETS REQUIREMENTS

API SL/CF

PRODUCT DESCRIPTION

LUKOIL LUXE SAE 20W-50, API SL/CF is a universal engine oil. The oil is based on high-quality mineral base stocks and efficient additive package of foreign manufacture.

APPLICATION

LUKOIL LUXE SAE 20W-50, API SL/CF is recommended for highly accelerated gasoline and diesel engines of passenger cars, light vans and trucks, which require the use of API SL/CF lubricants (or earlier operational classes).

LUKOIL LUXE SAE 20W-50, API SL/CF is designed especially for hot climate.

FEATURES AND BENEFITS

- High anti-oxidation and dispersing capabilities
- Protection of engine against high temperature deposits
- Robust anti-wear properties
- Reduces oil consumption and noise level during operation under high loads and temperatures

The product name in an order:

Multigrade Engine Oil LUKOIL LUXE SAE 20W-50, API SL/CF, STO 00044434-003-2005

TYPICAL TEST DATA

PROPERTY	Test method	LUKOIL LUXE SAE 20W-50, API SL/CF
Kinematic viscosity at 100 °C, mm ² /s	ASTM D445 / GOST 33 / GOST R 53708	21.31
Viscosity index	ASTM D2270 / GOST 25371	140
Apparent viscosity CCS at -15 °C, mPa·s	ASTM D5293 / GOST R 52559	6,100
Apparent viscosity MRV at -20 °C, mPa·s	ASTM D4684 / GOST R 52257	24,400
Flash Point, COC, °C	ASTM D92 / GOST 4333	244
Pour Point, °C	GOST 20287 B	-26
Noack evaporation loss, %	ASTM D5800 / DIN 51581-1	6.3

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO "LLK-International".