

LUKOIL LUXE TURBO DIESEL

semi-synthetic SAE 10W-40, API CF

High quality multigrade engine oil

MEETS REQUIREMENTS

API CF

PRODUCT DESCRIPTION

Semi-synthetic LUKOIL LUXE TURBO DIESEL SAE 10W-40, API CF is high quality multi-grade engine oil. It is designed for modern high-performance diesel engines, especially equipped with pump injectors. It is excellent for diesel engines in passenger cars, vans and light-duty trucks, including turbo-charged engines.

APPLICATION

Semi-synthetic LUKOIL LUXE TURBO DIESEL SAE 10W-40, API CF oil is recommended for four-stroke turbocharged diesel of passenger cars, vans and light-duty trucks.

BENEFITS

- Good low-temperature performance makes starting easier on cold conditions
- Protection of engine against wear, corrosion and high-temperature deposits on heavy duty city traffic
- High anti-oxidation and dispersing capabilities

The product name in an order:

Multigrade Semi-synthetic Engine Oil LUKOIL LUXE TURBO DIESEL SAE 10W-40, API CF, STO 00044434-003-2005

TYPICAL TEST DATA

PROPERTY	Test methods	LUKOIL LUXE TURBO DIESEL SAE 10W-40, API CF
Density at 15 °C, kg/m ³	GOST 3900 / ASTM D1298 / ASTM D4052	874
Kinematic viscosity at 100 °C, mm ² /s	ASTM D445 / GOST 33 / GOST R 53708	13.9
Kinematic viscosity at 40 °C, mm ² /s	ASTM D445 / GOST 33 / GOST R 53708	93.5
Viscosity Index	ASTM D2270 / GOST 25371	154
Apparent viscosity CCS at -25 °C, mPa·s	ASTM D5293 / GOST R 52559	5,390
Apparent viscosity MRV at -30 °C, mPa·s	ASTM D4684 / GOST R 52257	26,600
Total Base Number, mg KOH/1 g oil	ASTM D2896 / GOST 30050	8.0
Sulphated ash %	GOST 12417 / ASTM D874	1.0
Noack evaporation loss, %	ASTM D5800 / DIN 51581-1	11
Flash Point, COC, °C	GOST 4333 / ASTM D92	225
Pour Point, °C	GOST 20287 B	-33

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO "LLK-International".