

M-14V₂

Mono Grade Motor Oil for Low Power Diesel Engines

MEETS REQUIREMENTS

API CB

PRODUCT DESCRIPTION

M-14V₂ is mineral single grade motor oils, manufactured on a base of highly refined mineral base stocks and advanced additive package.

APPLICATION

M-14V₂ are designed for moderate power two- and four-stroke trunk piston diesel

engines of locomotive and marine equipment operating under heavy loads on distillate diesel fuels with sulfur content up to 0.5%, as well as for heavy-duty mine dump trucks.

BENEFITS

- Multipurpose performance
- Enhanced engine life

The product name in an order:

Motor oil for diesel engines M-14V₂, GOST 12337-84

TYPICAL TEST DATA

PROPERTY	Test methods	M-14V ₂
SAE Grade		40
Density at 20 °C, kg/m ³	GOST 3900	894.5
Kinematic viscosity at 100 °C, mm ² /s	GOST 33	13.99
Kinematic viscosity at 40 °C, mm ² /s	GOST 33	144.9
Viscosity index	GOST 25371	92
Flash Point, COC, °C	GOST 4333	243
Pour Point, °C	GOST 20287 B	-13
Total base number, mg KOH/1 g oil	GOST 11362	6.6

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances.