

LUKOIL GENESIS SPECIAL A5/B5 5W-30

Multi-grade fully synthetic motor oil for reduced fuel consumption

APPROVALS

API SL – licensed (API №2523)
Ford WSS-M2C-913-D
Renault RN 0700
Jaguar Land Rover ST JLR.03.5003

MEETS REQUIREMENTS

API CF
ACEA A5/B5, A1/B1
Ford WSS-M2C-913-A/B/C
Iveco 18-1811 S1

PRODUCT DESCRIPTION

LUKOIL GENESIS SPECIAL A5/B5 5W-30 is multi-grade fully synthetic motor oil of the latest generation with high fuel economy performance. The oil is designed for all modern high performance engines of passenger cars and light trucks including turbocharged which are used both over warranty and post-warranty periods of operation and served at car maintenance and service stations.

LUKOIL GENESIS SPECIAL A5/B5 5W-30 is produced using high-quality synthetic base stocks and advanced additive package providing high properties against oxidation and corrosion.

APPLICATION

LUKOIL GENESIS SPECIAL A5/B5 5W-30 is recommended for modern gasoline and diesel engines with direct fuel injection for severe

conditions and extended drain intervals. It is recommended for Ford and Renault engines which require oils with WSS-M2C913-D, C and RN 0700 performance levels accordingly.

BENEFITS

- Provides significant fuel economy and reduces exhaust gases emissions
- Maximum engine protection against wear in severe conditions of urban cycle
- Excellent resistance to oxidation and corrosion
- High detergent-dispersant properties
- Suitable for operation under high loads
- Prevents the formation of high- and low-temperature deposits on engine components
- Excellent low-temperature properties due to easy cold start

The product name in an order:

Motor oil LUKOIL GENESIS SPECIAL A5/B5 5W-30, STO 79345251-074-2015

TYPICAL TEST DATA

PROPERTY	Test methods	LUKOIL GENESIS SPECIAL A5/B5 5W-30
Density at 15 °C, kg/m ³	GOST R 51069 / ASTM D4052 / ASTM D1298	845.7
Kinematic viscosity at 100 °C, mm ² /s	GOST 33 / ASTM D445 / GOST R 53708	9.9
Viscosity index	GOST 25371 / ASTM D2270	175
Cold Cranking Viscosity, CCS at -30 °C, mPa·s	ASTM D5293 / GOST R 52559	3,264
Borderline Pumping Viscosity, MRV at -35 °C, mPa·s	ASTM D4684 / GOST R 52257	19,200
Total base number, mg KOH/1 g oil	GOST 30050 / ASTM D2896	10
Sulphated ash, %	GOST 12417 / ASTM D874	1.1
Noack evaporation loss, %	ASTM D5800 / DIN 51581-1	11
Flash Point, COC, °C	GOST 4333 / ASTM D92	220
Pour Point, °C	GOST 20287 B	-40

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO "LLK-International".