

LUKOIL GENESIS SPECIAL C2 5W-30

Fully synthetic Low SAPS motor oil

MEETS REQUIREMENTS

API SN/CF
ACEA C2, A5/B5, A1/B1
Fiat 9.55535-S1
PSA B71 2290
Renault RN 0700
Iveco 18-1811 SC1

PRODUCT DESCRIPTION

LUKOIL GENESIS SPECIAL C2 5W-30 is a fully synthetic motor oil of the latest generation. The oil is intended for year-round use in all modern engines of passenger cars and light trucks, especially fitted with Diesel Particulate Filter and which require low-viscous Low SAPS oils with reliable slipperly properties.

LUKOIL GENESIS SPECIAL C2 5W-30 is the low SAPS oil (low content of Sulfur, Phosphorus and Sulfated ash) on modern synthetic base oils.

APPLICATION

LUKOIL GENESIS SPECIAL C2 5W-30 is recommended for all-season operation in modern gasoline and diesel engines of Peugeot-Citroen cars according PSA B71 2290 oil specification, also in cars of Japanese and Korean manufacture according ACEA C2 performance level.

The product name in an order:

Motor oil LUKOIL GENESIS SPECIAL C2 5W-30, STO 79345251-074-2015

The product is recommended for car maintenance at service stations in warranty and post-warranty periods of operation.

BENEFITS

- Specially designed for Peugeot and Citroen cars
- Easy cold start at low temperatures
- High fuel efficiency due to specially selected synthetic base oils
- Maximum engine protection against wear in severe conditions of urban cycle
- Compatible with modern exhaust after-treatment systems which are sensitive to sulphated ash content
- Low sulphur and phosphorus content provides extended life of catalyst converter

TYPICAL TEST DATA

PROPERTY	Test methods	LUKOIL GENESIS SPECIAL C2 5W-30
Density at 15 °C, kg/m ³	GOST R 51069 / ASTM D4052 / ASTM D1298	847.3
Kinematic viscosity at 100 °C, mm ² /s	GOST 33 / ASTM D445 / GOST R 53708	10.93
Viscosity index	GOST 25371 / ASTM D2270	173
Cold Cranking Viscosity, CCS at -30 °C, mPa·s	ASTM D5293 / GOST R 52559	4,470
Borderline Pumping Viscosity, MRV at -35 °C, mPa·s	ASTM D4684 / GOST R 52257	16,800
Total base number, mg KOH/1 g oil	GOST 30050 / ASTM D2896	8.0
Sulphated ash, %	GOST 12417 / ASTM D874	0.8
Noack evaporation loss, %	ASTM D5800 / DIN 51581-1	10
Flash Point, COC, °C	GOST 4333 / ASTM D92	228
Pour Point, °C	GOST 20287 B	-46

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO "LLK-International".