

LUKOIL DOT 3

Brake and clutch fluid DOT 3

MEETS REQUIREMENTS

FMVSS 116 DOT 3

ISO 4925 class 3

SAE J 1703

PRODUCT DESCRIPTION

LUKOIL DOT 3 – high performance brake and clutch fluid designed for hydraulic brake actuation and clutch systems requiring DOT 3 fluids.

LUKOIL DOT 3 is compatible with any Russian DOT 3 brake fluids.

Product is manufactured according to STO 82851503-048-2013

APPLICATION

Hydraulic brake and clutch systems which are manufactured in Russia and abroad where OEM recommends DOT 3 brake fluids.

TYPICAL TEST DATA

PROPERTY	Test Method	LUKOIL DOT 3
Kinematic viscosity at 100 °C, mm ² /s	ASTM D445 / GOST 33 / GOST P 3708	1.8
Kinematic viscosity at 50 °C, mm ² /s	ASTM D445 / GOST 33 / GOST P 3708	6
Kinematic viscosity at - 40 °C, mm ² /s	ASTM D445 / GOST 33 / GOST P 3708	1,350
Dry boiling point, °C	c.11.3 of STO	231
Wet boiling point, °C	c.11.4 of STO	142
pH	c.11.6 of STO	9.6

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO "LLK-International".