

LUKOIL DOT 4

Brake and clutch fluid DOT 4

MEETS REQUIREMENTS

FMVSS 116 DOT 4
SAE J 1703

PRODUCT DESCRIPTION

LUKOIL DOT 4 – high performance liquid specially designed for brakes and clutches.

LUKOIL DOT 4 is compatible with the following brake fluids: DOT 3, DOT 4, “Neva”, “Rosa” and possess high thermal oxidation stability and excellent protection to the brake system components.

APPLICATION

Hydraulic brake systems which are manufactured in Russia and abroad where OEM recommends DOT 4 brake fluids.

Product is manufactured according to STO 82851503-048-2013

TYPICAL TEST DATA

PROPERTY	Test Method	LUKOIL DOT 4
Kinematic viscosity at 100 °C, mm ² /s	ASTM D445 / GOST 33 / GOST P 3708	2.2
Kinematic viscosity at - 40 °C, mm ² /s	ASTM D445 / GOST 33 / GOST P 3708	1,570
Dry boiling point, °C	c.11.3 of STO	255
Wet boiling point, °C	c.11.4 of STO	156
pH	c.11.6 of STO	8.85

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO “LLK-International”.