

LUKOIL GEYSER 30

High Quality Oil for Off-Road Vehicles

MEETS REQUIREMENTS

Caterpillar TO-4; **Allison** C-4; **API** MT-1; **ZF-TE-ML** 07F; **ZF-TE-ML** 03C; **Komatsu** ; **API** CF

PRODUCT DESCRIPTION

LUKOIL GEYSER MM 30 is an oil designed for heavy duty components of off-road vehicles. Produced on high quality base oil with multifunctional additives package, which provides smooth operation of gearboxes frictional components.

APPLICATION

LUKOIL GEYSER MM 30 is used in axle and final drives, as well as transmission components of heavy duty

applications, including off-road vehicles, where CAT TO-4 and Komatsu KES 07.868.1 oils are required. Can also be used in hydraulic systems, wet disk brakes and diesel engines (4T, 2T).

BENEFITS

- Universal applicability of oils
- Superior friction characteristics
- Excellent protection against wear and corrosion
- High antioxidant properties

The product name in an order:

Hydraulic oil LUKOIL GEYSER MM 30 (SAE 30), TU 0253-013-79345251-2008

TYPICAL TEST DATA

PROPERTY	Test methods	LUKOIL GEYSER 30
Density at 20 °C, kg/m ³	GOST 3900 / GOST R 51069 / ASTM D1298 / ASTM D4052	895.1
Kinematic viscosity at 40 °C, mm ² /s	ASTM D445	100.5
Kinematic viscosity at 100 °C, mm ² /s	ASTM D445	10.9
Viscosity index	ASTM D2270	94
Total Base Number, mg KOH/1 g oil	GOST 11362	7.5
Flash Point, COC, °C	ASTM D92	251
Pour Point, °C	GOST 20287 B	- 26.6

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO "LLK-International"