

LUKOIL GEYSER XLT 32

Premium hydraulic fluid for extremely low temperatures application

MEETS REQUIREMENTS

DIN 51524-3 (HVLP)

PRODUCT DESCRIPTION

LUKOIL GEYSER XLT 32 is hydraulic oil with excellent low-temperature properties. The oil is based on carefully selected base stocks and special additives package and has extremely high viscosity index (VI > 300).

APPLICATION

LUKOIL GEYSER XLT 32 is designed for application in the hydraulic system of off-road mobile equipment, forest machines as well as

various industrial equipment which operates in the winter season at arctic conditions.

BENEFITS

- Very high viscosity index and low pour point for use in Arctic conditions
- The minimum change of viscosity from temperature allows avoiding breakage of hydraulic equipment hoses
- Provides good wear protection for hydraulic pumps and engines

The product name in an order:

Hydraulic fluid LUKOIL GEYSER XLT 32, STO 79345251-182-2018

TYPICAL TEST DATA

PROPERTY	Test methods	LUKOIL GEYSER XLT 32
Kinematic viscosity at 40 °C, mm ² /s	ASTM D445	30.5
Kinematic viscosity at -30°C, mm ² /s	GOST 33 / GOST R 53708 / ASTM D445	752
Kinematic viscosity at -40 °C,mm ² /s	ASTM D445 / GOST 33 / GOST R 3708	1,875
Viscosity index	ASTM D2270	320
Flash Point, COC, °C	ASTM D92	121
Pour Point, °C	GOST 20287 B	-53

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO "LLK-International"