

LUKOIL CHAINSAW OIL

Multigrade special oil for all types of chainsaws

PRODUCT DESCRIPTION

LUKOIL CHAINSAW OIL is a multigrade special semi-synthetic oil for lubrication of harvester heads, chainsaws and small tools. Based on high-quality mineral and synthetic base oils blended with high performance special additives, which improve lubrication and adhesive properties.

APPLICATION

LUKOIL CHAINSAW OIL is recommended for lubrication of chainsaws, chain bars and sprocket-wheels of gasolines and electric handsaws of all types and also harvesting machines.

BENEFITS

- Stable oil film provides high antiwear and lubricating properties, which increase service life of chainsaw
- Provides excellent adhesion properties, which decrease oil splashing and oil consumption
- Effectively removes wood dust, chips and wood resin
- Low pour point
- Reduced chain vibration

TYPICAL TEST DATA

PROPERTY	Test methods	LUKOIL CHAINSAW OIL
Kinematic viscosity at 100 °C, mm ² /s	ASTM D445	13.05
Kinematic viscosity at 40 °C, mm ² /s	ASTM D445	102.9
Viscosity index	ASTM D2270	123
Flash Point, COC, °C	ASTM D92	232
Pour Point, °C	GOST 20287 B	-36
Density at 20 °C, kg/m ³	GOST 3900 / GOST R 51069 / ASTM D1298 / ASTM D4052	869.0

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO "LLK-International"