

PRODUCT INFORMATION

NAVIGO TPEO 15

Description

NAVIGO TPEO 15/30 and 15/40 are high quality detergent alkaline marine trunk piston engine oils.

Application

NAVIGO TPEO 15/30 and 15/40 are high quality alkaline lubricants recommended for highly rated marine trunk piston engines running on ISO 8217 type DMA/DMB/DMC fuels with a requirement of API CF diesel detergency.

They are also suitable for plain bearings of turbochargers, for most reduction gears, shaft bearings, stern tube and seals.

Features/Advantages and Benefits

- Excellent thermal and oxidation stability and detergency
 - Excellent deposit control
 - Leads to clean engine parts and spaces, meets API-CF requirements
 - Longer oil change intervals
- High level of API CF detergency performance
- Extended oil life due to efficient water separating properties and BN retention
- Rust and corrosion protection
- Excellent wear protection
- Meets major engine manufacturers' specifications

Typical Characteristics

Grade Name	Pour point °C	Flash point (COC) °C, min	Viscosity at 100°C cSt	SAE	Base number mgKOH/g
NAVIGO TPEO 15/30	-6	230	11.5	30	15
NAVIGO TPEO 15/40	-6	230	14.5	40	15

MARINE IN ALL WE DO!

Health and Safety

The Safety Data Sheet is available on request and describes the product in terms of safety in use, handling and transport. The product is not classified as dangerous according to the Regulations 1907/2006 and 1272/2008 or the Directive 1999/45/EC. When used as intended, this product does not pose significant health risks. Repeated exposure may cause skin dryness or cracking. In case of skin contact, immediately wash the affected area with plenty of soap and water. Remove contaminated clothes.

Handling and Packaging

The compatibility and miscibility with comparable products from other suppliers have been tested successfully by an independent institute. In order to benefit from full product performance the mixing of lubricants should be limited to a minimum.

Trunk piston engine oils should be continuously filtered in accordance with the equipment manufacturers' instructions. Their service life can be prolonged if the oil is maintained with a centrifugal purifier to remove water and insoluble components. Nevertheless, the oil change intervals of the equipment manufacturer are mandatory.

The products are available in bulk and drums of approximately 205 litres.

Further Information

For further information about LUKOIL Marine Lubricants please contact any representative of LUKOIL Marine Lubricants or visit our website www.lukoilmarine.com.

LUKOIL Marine Lubricants DMCC
January 2015