

# **LUKOIL GENESIS SPECIAL C4 5W-30**

Multi-grade synthetic low ash motor oil of the latest generation

#### **APPROVALS**

Renault RN 0720 MB-Approval 226.51

## **MEETS REQUIREMENTS**

ACEA C4

### **PRODUCT DESCRIPTION**

**LUKOIL GENESIS SPECIAL C4 5W-30** is multi-grade fully synthetic low-ash motor oil. The oil is especially recommended for Renault diesel engines which require the use of oils with Renault RN 0720 performance level. Recommended for car maintenance at service stations.

**LUKOIL GENESIS SPECIAL C4 5W-30** is intended for use in modern diesel engines including turbocharged and equipped with Diesel Particulate Filter (DPF). Recommended for Renault and Mercedes Benz diesel engines.

## **BENEFITS**

- Ensures long life of the diesel particulate filters and catalytic converters
- Excellent detergent-dispersant properties
- Provides excellent wear protection at severe operating conditions of the urban driving cycle
- High rate of fuel economy and emission lowering
- Easy cold start at low temperatures
- Recommended for Renault engines which require RN 0720 specification

The product name in an order:

Motor oil LUKOIL GENESIS SPECIAL C4 5W-30, STO 79345251-074-2015

Tel.: (495) 627-40-20

Fax: (495) 981-76-84

## **TYPICAL TEST DATA**

PROPERTY	Test methods	<b>LUKOIL GENESIS SPECIAL C4 5W-30</b>
Density at 20 °C, kg/m <sup>3</sup>	ASTM D7042	849
Kinematic viscosity at 100 °C, mm <sup>2</sup> /s	ASTM D7042	12.09
Viscosity index	ASTM D7042 / ASTM D2270	170
Cold Cranking Viscosity, CCS at -30 °C, mPa·s	ASTM D5293	5,600
Total base number, mg KOH/1 g oil	ASTM D2896	6.0
Sulphated ash, %	ASTM D874	0.39
Noack evaporation loss, %	ASTM D5800	10.1
Flash Point, COC, °C	ASTM D92	234
Pour Point, °C	ASTM D97	-39

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO "LLK-International".

