

# LUKOIL TOSOL SUPER A 65

Low-freezing coolant

## **MEETS REQUIREMENTS**

**GOST 28084-89**

## **PRODUCT DESCRIPTION**

**LUKOIL TOSOL SUPER A 65** is ready-for-use coolant with low pour point manufactured on a base of ethylene-glycol with anti-corrosion and anti-foam components and stabilizers. For use in car engines operated at temperature down to -65 °C.

The product effectively chills down an engine and protects the system against corrosion and scaling. Neutral to rubber hoses and sealants made of rubber and plastic.

## **APPLICATION**

**LUKOIL TOSOL SUPER A 65** is to be used in all modern car engine cooling system.

The product name in an order:

Low temperature coolant LUKOIL TOSOL SUPER A 65, STO 79345251-007-2008

## **TYPICAL TEST DATA**

PROPERTY	Test methods	LUKOIL TOSOL SUPER A 65
Density at 20°C, g/sm <sup>3</sup>	GOST 18995.1	1.085-1.100
Colour	GOST 28084, p.4.1	Blue
Boiling point, °C, min.	p.7.3 STO	108
Chilling point, °C, max.	GOST 28084, p.4.3	-65
Alkalinity, cm <sup>3</sup> , min.	GOST 28084, p.4.10	10

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO "LLK-International".