

# L GENESIS SPECIAL ADVANCED

Multi-grade engine oil based on synthetic technology for passenger cars

### **APPROVALS**

API SN-licensed (API №2523)

# **MEETS REQUIREMENTS**

**API** CF

**ACEA** A3/B4, A3/B3

**PSA** B71 2294, **PSA** B71 2300

Renault RN 0700/0710 MB-Approval 229.3 **VW** 502.00/505.00

**GM** LL-A/B-025

Fiat 9.55535-G2

#### PRODUCT DESCRIPTION

LUKOIL GENESIS SPECIAL ADVANCED 10W-40 is multi-grade engine oil based on synthetic technology for modern passenger cars passing maintenance operation at service stations.

# **APPLICATION**

The oil is designed for gasoline and diesel engines (without DPF) of modern and older passenger cars of foreign and domestic manufacture which are used under severe operating

It is recommended for use in engines of Volkswagen Group and Mercedes-Benz automobiles, passing maintenance at service station during warranty and out of warranty periods of operation.

#### BENEFITS

- Highest performance level according to API SN classification
- Synthetic base oil helps easy cold start-up
- Specially selected additives help to improve oil life under severe operating conditions (traffic jams, low fuel quality and severe climate)
- Advanced detergency and dispersancy as well as acid neutralizing properties provide cleanliness of the engine components

The product name in an order:

Motor oil LUKOIL GENESIS SPECIAL ADVANCED 10W-40, STO 79345251-074-2015

Tel.: (495) 627-40-20

Fax: (495) 981-76-84

# TYPICAL TEST DATA

PROPERTY	Test method	LUKOIL GENESIS SPECIAL ADVANCED 10W-40
Density at 20°C, kg/m <sup>3</sup>	GOST 3900 / ASTM D4052	857
Kinematic viscosity at 100°C, mm <sup>2</sup> /s	GOST 33 / ASTM D445 / GOST R 53708	13.7
Viscosity Index	GOST 25371 / ASTM D2270	158
Cold Cranking Viscosity (CCS), mPa·s	ASTM D5293 / GOST R 52559	4,900
Borderline Pumping Viscosity (MRV), mPa·s	ASTM D4684 / GOST R 52257	15,500
Total Base Number, mg KOH/1 g oil	GOST 30050 / ASTM D2896	10.8
Sulphated Ash, %	GOST 12417 / ASTM D874	1.2
Noack evaporation loss, %	ASTM D5800 / DIN 51581-1	9.9
Flash Point, COC, °C	GOST 4333 / ASTM D92	234
Pour Point, °C	GOST 20287 B	-47

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO "LLK-International".

member of: