

LUKOIL GENESIS SPECIAL A3/B4 5W-40

Multi-grade fully synthetic motor oil of the latest generation

Approvals

- API SN
- MB-Approval 229.5
- Renault RN 0700/0710

Meets requirements

- VW 502 00/505 00
- ACEA A3/B3, A3/B4
- API CF
- MB 226.5
- Fiat 9.55535-N2/Z2
- PSA B71 2296

Product description

LUKOIL GENESIS SPECIAL A3/B4 5W-40 is multi-grade fully synthetic motor oil with API SN/CF, ACEA A3/B4 performance levels. It is formulated on high-quality synthetic base oil and advanced additive technology. Recommended for service maintenance at service stations.

Application

LUKOIL GENESIS SPECIAL A3/B4 5W-40 is intended for use in modern gasoline and diesel engines including turbocharged ones.

Benefits

PROTECTION

Reliable engine protection in severe conditions of winter due to improved low-temperature properties

Provides excellent protection against wear in severe operating conditions

CLEANLINESS

Prevents the formation of high and low temperature deposits on engine components

ADJUSTEMENTS

Adjusted for severe conditions of urban cycle

The product name in an order: Motor Oil LUKOIL GENESIS SPECIAL A3/B4 5W-40, STO 79345251-074-2015

Typical test data

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO "LLK-International"

| Property | Test methods | Value |
|---|---------------------------|--------|
| Density at 15 °C, kg/m ³ | ASTM D1298 / ASTM D4052 | 845 |
| Kinematic viscosity at 100 °C, mm ² /s | ASTM D445 | 13.2 |
| Viscosity index | ASTM D2270 | 180 |
| Dynamic viscosity (CCS) at -30°C, mPa·s | ASTM D5293 / GOST R 52559 | 3,672 |
| Dynamic viscosity (MRV) at -35°C, mPa·s | ASTM D4684 / GOST R 52257 | 23,300 |
| Total Base Number, mg KOH/1 g oil | ASTM D2896 | 10.5 |
| Sulphated ash, % | ASTM D874 | 1.2 |
| Noack evaporation loss, % | ASTM D5800 / DIN 51581-1 | 9.7 |
| Flash Point, COC, °C | ASTM D92 | 222 |
| Pour Point, °C | GOST 20287 B | -40 |

27.12.2018* Page 1/1
 This document supersedes all previous versions

N3, Secteur 6, Bloc E,
 Avenue Mehdi Ben Barka,
 Hay Riad, 10000 Rabat,
 Morocco
www.lukoil-lubricants.ma

Tel.: (212) 537 57 26 57

Member of:

