

LUKOIL LUXE 15W-40

Universal passenger car engine oil

Approvals

- PJSC "ZMZ"
- PJSC "AVTOVAZ"

Meets requirements

- API SL/CF

Product description

LUKOIL LUXE 15W-40 - high quality engine oil for gasoline and diesel engines.

Application

LUKOIL LUXE 15W-40 is designed for use in gasoline and diesel engines of passenger cars, light commercial vehicles and light duty trucks, where recommended oil category is API SL/CF or below.

Benefits

PROTECTION

Promotes reliable engine protection

CLEANLINESS

Helps to reduce the formation of deposits and keeps the engine clean

RESISTANCE

Excellent resistance to oxidation and corrosion

The product name in an order: Multigrade engine oil LUKOIL LUXE SAE 15W-40, API SL/CF, STO 00044434-003-2005

Typical test data

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO "LLK-International"

Property	Test methods	Value
Density at 15 °C, kg/m ³	ASTM D1298 / ASTM D4052	869.3
Kinematic viscosity at 100 °C, mm ² /s	ASTM D445	13.27
Viscosity index	ASTM D2270	120
Cold Cranking Viscosity at -20°C, CCS, mPa·s	ASTM D5293 / GOST R 52559	6,360
Pumping Viscosity at -25°C (MRV), mPa·s	ASTM D4684 / GOST R 52257	27,100
Total Base Number, mg KOH/1 g oil	ASTM D2896	8.1
Noack evaporation loss, %	ASTM D5800 / DIN 51581-1	10.7
Flash Point, COC, °C	ASTM D92	210
Pour Point, °C	GOST 20287 B	-40