

## LUKOIL STANDARD 20W-50

Multigrade mineral engine oil for high mileage cars

### Meets requirements

- API SF
- API CC

### Product description

LUKOIL STANDARD 20W-50 – multigrade engine oil for gasoline and diesel engines. This oil is intended for use in high mileage classic cars.

### Application

LUKOIL STANDARD 20W-50 is adapted for use in passenger cars and light commercial vehicles.

### Benefits

#### PURIFICATION

Based on mineral oil with high grade purification

#### CLEANLINESS

Excellent detergent-dispersant properties

#### STABILITY

High thermal and oxidation stability

The product name in an order: Motor oil LUKOIL STANDARD SAE 20W-50, API SF/CC, STO 00044434-002-2005

### Typical test data

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO "LLK-International"

Property	Test methods	Value
Density at 15 °C, kg/m <sup>3</sup>	ASTM D1298 / ASTM D4052	898
Kinematic viscosity at 100 °C, mm <sup>2</sup> /s	ASTM D445	18.5
Kinematic viscosity at 40 °C, mm <sup>2</sup> /s	ASTM D445	159.5
Viscosity index	ASTM D2270	129
Dynamic viscosity (CCS) at -15°C, mPa·s	ASTM D5293 / GOST R 52559	5,770
Dynamic viscosity (MRV) at -20 °C, mPa·s	ASTM D4684 / GOST R 52257	23,100
Total Base Number, mg KOH/1 g oil	ASTM D2896	6.7
Sulphated ash, %	ASTM D874	1.0
Noack evaporation loss, %	ASTM D5800 / DIN 51581-1	4.8
Flash Point, COC, °C	ASTM D92	240
Pour Point, °C	GOST 20287 B	-25