

LUKOIL SUPER 20W-50

High-quality multigrade engine oil

Approvals

- JSC "ZMZ"
- PJSC "AVTOVAZ"

Meets requirements

- API SG
- API CD

Product description

LUKOIL SUPER 20W-50 is a mineral multigrade engine oil.

LUKOIL SUPER 20W-50 is based on highly purified mineral base stocks, which provide reliable engine performance in a wide range of temperatures and loads.

Application

LUKOIL SUPER 20W-50 is recommended for use in gasoline and diesel engines of passenger cars and light commercial vehicles.

Benefits

EVAPORATION

Carefully selected formulation minimizes evaporation loss

COLD START

Good low-temperature properties provide easy cold start

STABILITY

High thermal and oxidation stability

The product name in an order: Multigrade Engine Oil LUKOIL SUPER SAE 20W-50, API SG/CD, STO 00044434-001-2005

Typical test data

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO "LLK-International"

Property	Test methods	Value
Density at 15 °C, kg/m ³	ASTM D1298 / ASTM D4052	893
Kinematic viscosity at 100 °C, mm ² /s	ASTM D445	16.9
Viscosity index	ASTM D2270	124
Dynamic viscosity (CCS) at -15°C, mPa·s	ASTM D5293 / GOST R 52559	5,827
Dynamic viscosity (MRV) at -20 °C, mPa·s	ASTM D4684 / GOST R 52257	20,100
Total Base Number, mg KOH/1 g oil	ASTM D2896	8.5
Sulphated ash, %	ASTM D874	1.1
Noack evaporation loss, %	ASTM D5800 / DIN 51581-1	4.7
Flash Point, COC, °C	ASTM D92	240
Pour Point, °C	GOST 20287 B	-22

18.04.2019* Page 1/1

This document supersedes all previous versions

N3, Secteur 6, Bloc E,
Avenue Mehdi Ben Barka,
Hay Riad, 10000 Rabat,
Morocco
www.lukoil-lubricants.ma

Tel.: (212) 537 57 26 57

Member of:

