

## LUKOIL ATF IIIG

High performance semi-synthetic automatic transmission fluid

### Approvals

- MAN 339 Type V1/Z1/L1
- VOITH H55.6335.XX
- ZF TE-ML 04D/14A

### Meet requirements

- MAN 339 Type F/D
- VOLVO 97340/97341
- RBAS TE-ML 09
- GM DEXRON IID/IIIG
- ZF TE-ML 11A/11B/17C
- Caterpillar TO-2
- Allison C-4

### Product description

LUKOIL ATF IIIG is a universal semi-synthetic automatic transmission fluid designed for both passenger cars and heavy-duty applications. LUKOIL ATF IIIG has excellent low temperature fluidity and delivers high performance in a wide temperature range due to high viscosity index.

LUKOIL ATF IIIG offers excellent corrosion and wear protection, good antifoaming properties, thermal and oxidation stability. LUKOIL ATF IIIG is designed to meet and exceed the requirements of the world's leading original equipment manufacturers.

### Application

LUKOIL ATF IIIG is recommended for use in step-type automatic transmission systems of both passenger cars and on- and off-highway vehicles, where Dexron® IIIG products are specified.

The product name in an order: Automatic Transmission Oil LUKOIL ATF IIIG, TU 0253-030-00148599-2005

### Typical test data

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO "LLK-International"

Property	Test methods	Value
Appearance	-	Transparent red liquid
Density at 15 °C, kg/m <sup>3</sup>	ASTM D1298 / ASTM D4052	862
Kinematic viscosity at 100 °C, mm <sup>2</sup> /s	ASTM D445	7.44
Kinematic viscosity at 40 °C, mm <sup>2</sup> /s	ASTM D445	36.7
Viscosity index	ASTM D2270	172
Brookfield Viscosity at -40 °C, mPa·s	ASTM D2983	14,897
Flash Point, COC, °C	ASTM D92	205
Pour Point, °C	GOST 20287 B	-56