

LUKOIL TRANSMISSION TM-5 SAE 85W-90

High quality API GL-5 gear oil

Approvals

- ZF TE-ML 16B/17B/19B/21A
- PJSC "AVTOVAZ"

Meets requirements

- API GL-5
- ZF TE-ML 05A/07A/08/12E/16C
- MAN 342 M1/M2
- MIL L-2105D
- Ferrit

Product description

LUKOIL TRANSMISSION TM-5 SAE 85W-90 is a multi-grade mineral gear oil for manual transmissions of passenger cars, commercial vehicles and other mobile equipment where API GL-5 oils are recommended.

LUKOIL TRANSMISSION TM-5 SAE 85W-90 is based on highly refined mineral oils blended with robust additive package with excellent antiwear and EP properties.

Application

LUKOIL TRANSMISSION TM-5 SAE 85W-90 is recommended for use in axles with spur, spiral bevel, and hypoid gears of passenger cars, commercial vehicles and off-highway equipment.

Warning!: This oil is not recommended for use in manual gearboxes with brass synchronizers.

Benefits

ANTI-WEAR

Excellent extreme pressure and anti-wear properties

FILM THICKNESS

Sustained film thickness even at high loads

STABILITY

Excellent thermal-oxidative stability

ANTI-FOAMING

Excellent anti-foaming properties

The product name in an order: Oil LUKOIL TRANSMISSION TM-5 SAE 85W-90, STO 00044434-009-2006

Typical test data

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO "LLK-International"

Property	Test methods	Value
Density at 15 °C, kg/m ³	ASTM D1298 / ASTM D4052	904
Kinematic viscosity at 100 °C, mm ² /s	ASTM D445	17.5
Kinematic viscosity at 40 °C, mm ² /s	ASTM D445	190.5
Viscosity index	ASTM D2270	100
Flash Point, COC, °C	ASTM D92	219
Pour Point, °C	GOST 20287 B	-25