

LUKOIL VERSO 10W-30

High Quality Universal Tractor Transmission Oil

Approvals

- CMS M1145

Meets requirements

- API GL-4;
- I.H.C. B5 & B6 Hydran;
- White Q-1705/1766/1722/1826;
- KUBOTA UDT;
- JCMAS HK P-041;
- CMS NH 410 B/420 A;
- CMS M1143;
- CNH MAT3525;
- CASE MS 1204/1206/1207/1209;
- FORD ESN-M2C86-B;
- FORD ESN-M2C134-D;
- FORD ESN-M2C86-A;
- John Deere JDM J20C;
- Valtra G2-08; Denison
- HF-0/HF-1/HF-2;
- Oliver Type 55/Type5J/Q1802;
- CMS M1135;
- Fiat AF 87;
- Sauer Sunstrand/Danfoss Hydro Static ;
- Vickers/Eaton I-280-S & M2950S ;
- Allison C-4

Product description

LUKOIL VERSO 10W-30 is high-performance universal transmission oil (UTTO) manufactured using highly refined mineral blended with advanced additive package improving oil performance.

Application

LUKOIL VERSO 10W-30 is recommended for use in transmissions, hydraulic and oil-immersed brakes and other ancillary systems fitted to tractors and off-road equipment, operated in wide temperature interval.

Benefits

ANTI-WEAR

Excellent extreme pressure and anti-wear properties

FILM THICKNESS

Sustained film thickness even at high loads

STABILITY

Excellent thermal-oxidative stability

ANTI-FOAMING

Excellent anti-foaming properties

The product name in an order: Universal tractor oil LUKOIL VERSO SAE 10W-30, STO 79345251-022-2009

Typical test data

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO "LLK-International"

Property	Test methods	Value
Density at 15 °C, kg/m ³	ASTM D1298 / ASTM D4052	868.8
Kinematic viscosity at 100 °C, mm ² /s	ASTM D445	10.5
Kinematic viscosity at 40 °C, mm ² /s	ASTM D445	71.8
Viscosity index	ASTM D2270	136
Dynamic viscosity at 35 °C	GOST 1929	54,401
Total Base Number, mg KOH/1 g oil	GOST 11362	7.8
Flash Point, COC, °C	ASTM D92	245
Pour Point, °C	GOST 20287 B	-37