

## LUKOIL GEYSER MM 30

High Quality Oil for Off-Road Vehicles

### Meets requirements

- API MT-1
- API CF
- ZF TE-ML 03C, 07F
- Caterpillar TO-4
- Komatsu KES 07.868-1
- Allison C-4

### Product description

LUKOIL GEYSER MM 30 is an oil designed for heavy duty components of off-road vehicles. Produced on high quality base oil with involvement multifunctional additive package, which provides smooth operation of gearboxes frictional components.

### Application

LUKOIL GEYSER MM 30 is used in axle and final drives, as well as transmission components of heavy-duty applications, including off-road vehicles, where CAT TO-4 and Komatsu KES 07.868.1 oils are required. Can also be used in hydraulic systems and wet disk brakes.

### Benefits

#### UNIVERSAL

Universal applicability of oils

#### PROTECTION

Superior friction characteristics

Excellent protection against wear and corrosion

High antioxidant properties

The product name in an order: Hydraulic oil LUKOIL GEYSER MM 30 (SAE 30), TU 0253-013-79345251-2008

### Typical test data

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO "LLK-International"

Property	Test methods	Value
Density at 20 °C, kg/m <sup>3</sup>	GOST 3900 / GOST R 51069 / ASTM D1298 / ASTM D4052	895.1
Kinematic viscosity at 40 °C, mm <sup>2</sup> /s	ASTM D445	100.5
Kinematic viscosity at 100 °C, mm <sup>2</sup> /s	ASTM D445	10.9
Viscosity index	ASTM D2270	94
Total Base Number, mg KOH/1 g oil	GOST 11362	7.5
Flash Point, COC, °C	ASTM D92	251
Pour Point, °C	GOST 20287 B	-26.6