

LUKOIL GEYSER MM 10 (10W)

High performance semi-synthetic automatic transmission fluid

Meet requirements

- API CF; API MT-1
- Caterpillar TO-4
- ZF TE-ML 03C
- Komatsu KES 07.868-1
- Allison C-4

Product description

LUKOIL GEYSER MM 10 is an oil designed for heavy duty components of off-road vehicles.

Produced on high quality base oil with involvement multifunctional additive package, which provides smooth operation of gearboxes frictional components.

Application

LUKOIL GEYSER MM 10 is used in axle and final drives, as well as transmission components of heavy-duty applications, including off-road vehicles, where CAT TO-4 and Komatsu KES 07.868.1 oils are required. Can also be used in hydraulic systems, wet disk brakes and diesel engines (4T, 2T).

The product name in an order: Hydraulic oil LUKOIL GEYSER MM 10 (SAE 10W), TU 0253-013-79345251-2008

Typical test data

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO "LLK-International"

Property	Test methods	Value
Density at 20 °C, kg/m ³	GOST 3900 / GOST R 51069 / ASTM D1298 / ASTM D4052	880.6
Kinematic viscosity at 40 °C, mm ² /s	ASTM D445	46.1
Kinematic viscosity at 100 °C, mm ² /s	ASTM D445	7.2
Viscosity index	ASTM D2270	108
Total Base Number, mg KOH/1 g oil	GOST 11362	7.5
Flash Point, COC, °C	ASTM D92	235
Pour Point, °C	GOST 20287 B	-36.8