

## LUKOIL MOTO 4T 20W-50

### Multigrade 4-Stroke Small Engine oil

#### Approvals

- HUTER

#### Meet requirements

- API SG

#### Product description

LUKOIL MOTO 4T 20W-50 is a multigrade mineral engine oil for 4-stroke engines of motorcycles, scooters, mopeds and other two-wheeled motor vehicles.

LUKOIL MOTO 4T 20W-50 is produced on high-quality base oil and balanced additive package of foreign manufacturer. It has improved detergency, anti-wear, antifoam properties and resistance to oxidation and corrosion.

#### Application

LUKOIL MOTO 4T 20W-50 is intended for use in 4-stroke engines of scooters, mopeds, motorcycles and ATVs requiring API SG performance level, it is also recommended for motorbike transmissions and clutches which need engine oil lubrication.

LUKOIL MOTO 4T 20W-50 especially recommended for machinery, operated in hot climate

The product name in an order: Motor oil LUKOIL MOTO 4T SAE 20W-50, API SG, STO 79345251-061-2014

#### Typical test data

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO "LLK-International"

Property	Test methods	Value
Density at 15 °C, kg/m <sup>3</sup>	ASTM D1298 / ASTM D4052	881.7
Kinematic viscosity at 100 °C, mm <sup>2</sup> /s	ASTM D445	19.3
Viscosity index	ASTM D2270	136
Total Base Number, mg KOH/1 g oil	ASTM D2896	5.2
Sulphated ash, %	ASTM D874	0.71
Noack evaporation loss, %	ASTM D5800 / DIN 51581-1	6.1
Flash Point, COC, °C	ASTM D92	244