

LUKOIL ATF SYNTH MULTI

High performance fluid for passenger car and commercial vehicles automatic transmissions

APPROVALS

MB-Approval 236.6
ZF TE-ML 04D, 14B, 16L, 20B (ZF001944)
Volvo 97341
MAN 339 Types L1, V2, Z2, Z11
Voith H55.6336.xx

MEETS REQUIREMENTS

GM Dexron IIIH, IIIG, IID
Ford Mercon V
Ford Mercon
Allison C-4, TES-295, TES-389
JASO 1-A
Volvo 97340

PRODUCT DESCRIPTION

LUKOIL ATF SYNTH MULTI is a high quality universal automatic transmission fluid. This fluid was designed in respect of tough demands of leading world original equipment manufacturers and suitable for use in both of conventional and modern types of automatic transmission.

LUKOIL ATF SYNTH MULTI is suitable for vehicles of as North American as European manufacturers.

LUKOIL ATF SYNTH MULTI is recommended for service filling in foreign and domestic vehicles within warranty and post warranty periods.

APPLICATION

LUKOIL ATF SYNTH MULTI is recommended for step-type passenger car and commercial vehicles automatic transmissions where Dexron® IIIH or previous performance levels are required. It also can be used as power steering fluid.

BENEFITS

- Demonstrates stable antifriction properties and smooth shifting without vibration
- Possesses excellent thermal oxidative stability and maintains all properties at high level even in case of extended drain interval
- Provides extended clutch life
- Demonstrates improved lubrication and low temperature fluidity
- Optimal viscosity ensures prompt response of electrohydraulic controlling system

Additionally, **LUKOIL ATF SYNTH MULTI** possesses low dependence of viscosity on temperature (high viscosity index), excellent anti-aging properties and high resistance to foaming. This fluid does not have negative impact on seal materials. Improved anti corrosion reliably properties protect all equipment components.

The product name in an order:

Automatic Transmission Fluid LUKOIL ATF SYTNH MULTI, STO 79345251-038-2013

TYPICAL TEST DATA

PROPERTY	Test method	LUKOIL ATF SYNTH MULTI
Appearance	p.7.3 STO	Transparent red liquid
Density at 20 °C, kg/m ³	ASTM D4052 / GOST 3900	850
Kinematic Viscosity at 40 °C, mm ² /s	ASTM D445 / GOST 33 / GOST R 53708	36.8
Kinematic Viscosity at 100 °C, mm ² /s	ASTM D445 / GOST 33 / GOST R 53708	7.5
Viscosity Index	ASTM D2270 / GOST 25371	178
Brookfield Viscosity at -40 °C, mPa:s	ASTM D2983	11,960
Flash Point, COC, °C	ASTM D92 / GOST 4333	198
Pour Point, °C	GOST 20287 B	-50

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO "LLK-International".