

LUKOIL MOTO 2T

Two-stroke small engine oil

APPROVALS

HUTER

MEETS REQUIREMENTS

API TC
JASO FB
ISO E-GB

PRODUCT DESCRIPTION

LUKOIL MOTO 2T – modern high-quality mineral multigrade oil, designed for 2-Stroke gasoline engines of motorcycles, mopeds, scooters and snowmobiles.

LUKOIL MOTO 2T has good detergent, antioxidant and antiwear properties, which guarantee excellent engine performance under any conditions of operation.

LUKOIL MOTO 2T is formulated with high-quality base stocks and highly-effective advanced ashless package of additives, which provides perfect protection of the engine even

under the most severe conditions of operation, significantly decreases risk of sludge and deposits formation in outlet system, reduces the disruption of spark plugs and the risk of surface ignition, provides greater engine efficiency, decreases fuel consumption. Due to the careful formulation, **LUKOIL MOTO 2T** is virtually smokeless, and safe for the Environment.

APPLICATION

LUKOIL MOTO 2T is recommended for using in modern two-stroke engines of motorcycles, mopeds, scooters and snowmobiles. Proportion of the mixing must meet to the Operation and maintenance manual, but normally it is fuel:oil = 50:1

The product name in an order:

Motor oil for two-stroke gasoline engines LUKOIL MOTO 2T, STO 79345251-002-2008

TYPICAL TEST DATA

| PROPERTY | Test method | LUKOIL MOTO 2T |
|---|--|----------------|
| Density at 15 °C, kg/m ³ | ASTM D4052 / ASTM D1298 / GOST R 51069 | 894 |
| Kinematic viscosity at 100 °C, mm ² /s | ASTM D445 / GOST 33 | 14.5 |
| Viscosity Index | ASTM D2270 / GOST 25371 | 94 |
| Total base number, mg KOH/1 g oil | ASTM D2896 / GOST 11362 / GOST 30050 | 1.4 |
| Sulphated ash, % | ASTM D874 / GOST 12417 | 0.19 |
| Flash Point, COC, °C | ASTM D92 / GOST 4333 | 242 |
| Pour Point, °C | GOST 20287 B | -17 |

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO "LLK-International".