

LUKOIL GENESIS ARMORTECH JP 5W-30

Fully synthetic engine oil for Japanese cars

Approvals

- API SN, SN-RC
- ILSAC GF-5

Meets requirements

- Ford WSS-M2C-929-A

Product description

Fully synthetic engine oil for modern gasoline engines of Japanese cars, including engines equipped with turbocharger and Three Way Catalyst. Formulated with DuraMax[®] innovative technology.

Application

Recommended for all-season use in gasoline engines equipped with Three Way Catalyst of Japanese OEMs: Toyota, Honda, Infinity, Lexus, Mazda, Nissan, Suzuki, Subaru, Acura and others (both during warranty and afterwarranty periods). The oil can also be used in any other engines, which require API SN, ILSAC GF-5 performance level and SAE 5W-30 viscosity.

Benefits

ADVANCED FUEL ECONOMY

Excellent fuel economy due to optimal viscometric characteristics

MAXIMUM PRETECTION

Maximum protection against wear at severe conditions of urban driving cycle

LOW CONSUMPTION

Carefully selected formulation minimizes evaporation loss

The product name in an order: Engine oil LUKOIL GENESIS ARMORTECH JP 5W-30, STO 79345251-185-2019

Typical test data

The information given in the typical data does not constitute a specification and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO «LLK-International»

Property	Test methods	Value
Density at 15 °C, kg/m ³	ASTM D1298 / ASTM D4052	848.5
Viscosity index	ASTM D2270	178
Kinematic viscosity at 100 °C, mm ² /s	ASTM D445	10.4
Dynamic viscosity (CCS) at -30°C, mPa·s	ASTM D5293 / GOST R 52559	3,378
Cold Cranking Viscosity (CCS) at -35 °C, mPa·s	ASTM D5293 / GOST R 52559	16,057
Total Base Number, mg KOH/1 g oil	ASTM D2896	8.4
Sulphated ash, %	ASTM D874	0.9
Noack evaporation loss, %	ASTM D5800 / DIN 51581-1	11
Flash Point, COC, °C	ASTM D92	228
Pour Point, °C	GOST 20287 B	-41