

LUKOIL GENESIS SPECIAL A5/B5 0W-30

Multi-grade fully synthetic motor oil for reduced fuel consumption

APPROVALS

VOLVO 95200377

MEETS REQUIREMENTS

API SL/CF

ACEA A5/B5

Renault RN 0700

PRODUCT DESCRIPTION

LUKOIL GENESIS SPECIAL A5/B5 0W-30 is multi-grade fully synthetic motor oil of the latest generation with high fuel economy and excellent low-temperature performance. The oil is designed for all modern highly accelerated engines of passenger cars and light trucks including turbo-charged which are used both over warranty and post-warranty periods of operation and served at car maintenance and service stations.

LUKOIL GENESIS SPECIAL A5/B5 0W-30 is produced using high-quality synthetic base stocks and high efficiency additive package providing increased fuel economy.

APPLICATION

LUKOIL GENESIS SPECIAL A5/B5 0W-30 is recommended for year-round usage in modern gasoline and diesel engines with direct fuel injection, operated in extreme conditions.

The product is recommended for VOLVO engines (except 4-stroke ones which require VCC-RBS0-2AE) and TOYOTA engines, which require oils with ACEA A5/B5 performance level and SAE 0W-30 viscosity grade, and other OEMs, which require API SL/CF or ACEA A5/B5 oil performance level. Suitable for use in Renault engines without DPf.

BENEFITS

- Provides significant fuel economy and reduces exhaust gases emissions
- Maximum engine protection against wear in severe conditions of urban cycle
- Excellent resistance to oxidation and corrosion
- High detergent-dispersant properties
- Specially designed for operation under increased loads
- Prevents the formation of high- and low-temperature deposits on engine components
- Facilitates easy cold start at extremely cold temperatures

The product name in an order:

Motor oil LUKOIL GENESIS SPECIAL A5/B5 0W-30, STO 79345251-074-2015

TYPICAL TEST DATA

PROPERTY	Test methods	LUKOIL GENESIS SPECIAL A5/B5 0W-30
Density at 20 °C, kg/m ³	GOST R 51069 / ASTM D4052 / ASTM D1298	839.0
Kinematic viscosity at 100 °C, mm ² /s	GOST 33 / ASTM D445 / GOST R 53708	10.27
Viscosity index	GOST 25371 / ASTM D2270	184
Cold Cranking Viscosity, CCS at -35 °C, mPa·s	ASTM D5293 / GOST R 52559	5,324
Borderline Pumping Viscosity, MRV at -40 °C, mPa·s	ASTM D4684 / GOST R 52257	30,700
Total base number, mg KOH/1 g oil	GOST 30050 / ASTM D2896	10.0
Sulphated ash, %	GOST 12417 / ASTM D874	1.07
Noack evaporation loss, %	ASTM D5800 / DIN 51581-1	12.1
Flash Point, COC, °C	GOST 4333 / ASTM D92	227
Pour Point, °C	GOST 20287 B	-51

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO "LLK-International".