

## LUKOIL MOTO 2T

### Two-stroke small engine oil

#### Approvals

- HUTER

#### Meets requirements

- API TC
- JASO FB
- ISO L-EGB

#### Product description

High-quality mineral oil intended for use in two-stroke gasoline engines of motorcycles, scooters, mopeds, etc. Formulated with high-quality base oil and highly effective modern low-ash additive package, which provides maximum engine protection in all operating conditions and significantly decreases risk of sludge and deposits formation in outlet system.

#### Application

Recommended for using in modern two-stroke engines of motorcycles, mopeds and scooters.

Proportion of the mixing must meet to the Operation and maintenance manual, but normally it is fuel:oil = 50:1

The product name in an order: Motor oil for two-stroke gasoline engines LUKOIL MOTO 2T, STO 79345251-002-2008

#### Typical test data

The information given in the typical data does not constitute a specification and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO «LLK-International»

Property	Test methods	Value
Density at 15 °C, kg/m <sup>3</sup>	ASTM D1298 / ASTM D4052	894
Kinematic viscosity at 100 °C, mm <sup>2</sup> /s	ASTM D445	14.5
Viscosity index	ASTM D2270	94
Total Base Number, mg KOH/1 g oil	ASTM D2896	1.4
Sulphated ash, %	ASTM D874	0.19
Flash Point, COC, °C	ASTM D92	242
Pour Point, °C	GOST 20287 B	-17