

LUKOIL OUTBOARD 4T 10W-40

Motor oil for four-stroke gasoline engines of watercrafts

Meets requirements

- API SL
- NMMA FC-W

Product description

High-quality semi-synthetic motor oil for four-stroke gasoline engines of launches, yachts, jet skis and motor boats. It has effective lubricating, detergency, anti-wear properties and improved anticorrosion properties.

Application

Recommended for modern four-stroke highly accelerated outboard and water-jet motors with water and air cooling of launches, yachts, jet skis, motor boats and any other engines, which require NMMA (National Marine Manufacturing Association) FC-W lubricants.

Benefits

RELIABLE PROTECTION

Excellent deposit and wear control improves engine reliability and helps to extend the service interval

ENGINE CLEANLINESS

Helps to reduce the formation of deposits and keeps the engine clean

STABLE VISCOSITY

Exceptional resistance to degradation of thickener ensures stable viscosity during the whole oil life

The product name in an order: Motor oil LUKOIL OUTBOARD 4T SAE 10W-40, STO 79345251-094-2016

Typical test data

The information given in the typical data does not constitute a specification and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO «LLK-International»

Property	Test methods	Value
Kinematic viscosity at 100 °C, mm ² /s	ASTM D445	12.6
Viscosity index	ASTM D2270	150
Flash Point, COC, °C	ASTM D92	232
Pour Point, °C	GOST 20287 B	-32
Total Base Number, mg KOH/1 g oil	ASTM D2896	7.1
Sulphated ash, %	ASTM D874	0.8
Density at 20 °C, kg/m ³	ASTM D4052	867