

LUKOIL GARDEN 2T

Mineral oil for two-stroke engines of garden equipment

Meets requirements

- API TC
- JASO FB
- ISO L-EGB

Product description

Modern mineral oil intended for use as a component of a fuel-oil mixture of small two-stroke gasoline engines in garden equipment. It has good detergent, lubricating and antiwear properties, which guarantee excellent engine performance under any conditions of operation.

Application

Recommended for use in modern two-stroke engines of garden tools and garden equipment: lawn mowers, chainsaws, motor cultivators, walk-behind tractors, trimmers, etc.

Proportion of the mixing must meet to the Operation and maintenance manual, but normally it is fuel:oil = 50:1

The product name in an order: Motor oil LUKOIL GARDEN 2T, STO 79345251-095-2016

Typical test data

The information given in the typical data does not constitute a specification and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO «LLK-International»

Property	Test methods	Value
Kinematic viscosity at 100 °C, mm ² /s	ASTM D445	14.0
Viscosity index	ASTM D2270	96
Total Base Number, mg KOH/1 g oil	ASTM D2896	1.1
Sulphated ash, %	ASTM D874	0.14
Flash Point, COC, °C	ASTM D92	257
Pour Point, °C	GOST 20287 B	-16
Density at 20 °C, kg/m ³	ASTM D4052	887