

LUKOIL GARDEN 4T 30

Four-stroke small engine oil for garden equipment

Meets requirements

- API SG

Product description

Modern mineral oil, designed for four-stroke gasoline small engines of garden and agricultural equipment. Formulated with high-quality base stocks and highly effective additive package.

Application

Recommended for modern 4-Stroke engines lawn mowers, cultivators, tillers, generators, mini tractors and other garden and agricultural equipment, where API SG oils are recommended.

Benefits

MAXIMUM PROTECTION

Excellent extreme pressure and anti-wear properties

ENGINE CLEANLINESS

The optimum level of sulfate ash provides a low level of deposits in the engine

The product name in an order: Motor oil LUKOIL GARDEN 4T SAE 30, STO 79345251-095-2016

Typical test data

The information given in the typical data does not constitute a specification and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO «LLK-International»

Property	Test methods	Value
Kinematic viscosity at 100 °C, mm ² /s	ASTM D445	10.7
Viscosity index	ASTM D2270	106
Flash Point, COC, °C	ASTM D92	234
Pour Point, °C	GOST 20287 B	-25
Total Base Number, mg KOH/1 g oil	ASTM D2896	5.5
Sulphated ash, %	ASTM D874	0.77
Density at 20 °C, kg/m ³	ASTM D4052	882