

LUKOIL CHAINSAW OIL

Multigrade special oil for all types of chainsaws

Product description

Multigrade special semi-synthetic oil for lubrication of saw chains of harvesting heads and hand tools, based of high-quality mineral and synthetic base oils blended with high performance special additives which improve lubricity and adhesion properties.

Application

Recommended for the lubrication of saw chains, tires and the drive sprocket of all types of gasoline and electric hand saws, as well as forestry equipment.

Benefits

GOOD ANTI-WEAR PROPERTIES

Stable oil film provides high antiwear and lubricating properties, which increase service life of chainsaw

EXCELLENT ADHESION

Provides excellent adhesion properties, which decrease oil splashing and oil consumption

SMOOTH OPERATIONS

Reduced chain vibration

The product name in an order: Oil for saw LUKOIL CHAINSAW OIL, STO 79345251-136-2018

Typical test data

The information given in the typical data does not constitute a specification and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO «LLK-International»

Property	Test methods	Value
Kinematic viscosity at 100 °C, mm ² /s	ASTM D445	13.05
Viscosity index	ASTM D2270	123
Flash Point, COC, °C	ASTM D92	232
Pour Point, °C	GOST 20287 B	-36
Density at 20 °C, kg/m ³	ASTM D4052	869
Water content, weight %	GOST 2477	null