

## LUKOIL MOTO 4T 10W-40

### Four-stroke small engine oil

#### Approvals

- HUTER

#### Meets requirements

- API SL
- JASO MA2

#### Product description

High-quality semi-synthetic oil intended for use in four-stroke gasoline engines of motorcycles, mopeds, scooters, snowmobiles, ATVs and other motor vehicles. Provides maximum engine protection, excellent transmission and clutch performance, has excellent detergent and antioxidant properties, improved anti-wear, anti-corrosion and anti-foam properties.

#### Application

Recommended for use in modern four-stroke engines of motorcycles, scooters and snowmobiles, in which the manufacturer recommends using oils of classes API SL and below, JASO MA2. Used to lubricate the transmissions and clutches of modern motorcycles that require lubrication with engine oils.

#### Benefits

##### STABLE WET GRIP PERFORMANCE

High friction index minimizes the possibility of friction plates slippage

##### ENGINE CLEANLINESS

Helps to reduce the formation of deposits and keeps the engine clean

##### STABLE VISCOSITY

Exceptional resistance to degradation of thickener ensures stable viscosity during the whole oil life

The product name in an order: Motor oil LUKOIL MOTO 4T SAE 10W-40, API SL, STO 79345251-061-2014

#### Typical test data

The information given in the typical data does not constitute a specification and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO «LLK-International»

Property	Test methods	Value
Kinematic viscosity at 100 °C, mm <sup>2</sup> /s	ASTM D445	12.6
Viscosity index	ASTM D2270	150
Flash Point, COC, °C	ASTM D92	232
Pour Point, °C	GOST 20287 B	-32
Total Base Number, mg KOH/1 g oil	ASTM D2896	7.1
Sulphated ash, %	ASTM D874	0.8
Density at 20 °C, kg/m <sup>3</sup>	ASTM D4052	867