

LUKOIL TRANSMISSION LDI 75W-80

High performance multi-grade synthetic transmission oil with fuel economy properties

APPROVALS

MAN 341 Type E-3
MAN 341 Type Z-4
ZF TE-ML 02L, 08, 16K (ZF001767)

MEETS REQUIREMENTS

API GL-4
DAF
IVECO
MB 235.4
RENAULT
VOLVO 97305

PRODUCT DESCRIPTION

LUKOIL TRANSMISSION LDI 75W-80 is high performance multi-grade synthetic transmission oil with fuel economy properties for extremely extended drain intervals. It is recommended for bus and truck ZF Friedrichshafen AG manual transmissions including fitted with an intarder.

Due to superior aging resistibility **LUKOIL TRANSMISSION LDI 75W-80** is appropriate for extended drain intervals, especially for commercial vehicles.

Modern high performance anti-wear and anti-corrosion additives create lasting oil film on a detail surface, sustaining transmission life.

Outstanding low temperature properties and viscosity rating of **LUKOIL TRANSMISSION LDI 75W-80** ensure an exceptional comfort of smooth gear shifting. The product has extraordinary low pour point.

APPLICATION

LUKOIL TRANSMISSION LDI 75W-80 is recommended for extremely long drain intervals especially for manual synchromesh gearboxes with or without intarders.

TYPICAL TEST DATA

PROPERTY	Test methods	LUKOIL TRANSMISSION LDI
Viscosity grade	ASTM D4052	75W-80
Flash Point, COC, °C	ASTM D92	230
Pour Point, °C	SAE J 306	-42
Kinematic viscosity at 40 °C, mm ² /s	ASTM D7042	66
Kinematic viscosity at 100 °C, mm ² /s	ASTM D7042	9,5
Viscosity index	ASTM D7042 / ASTM D2270	155
Density at 15 °C, kg/m ³	ASTM D97	862

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO "LLK-International".