

## LUKOIL STANDARD 15W-40

### Multigrade mineral engine oil

#### Meets requirements

- API SF/CC

#### Product description

Multigrade engine oil for gasoline and diesel engines. This oil is intended for use in high-mileage classic cars which are characterized by excessive oil consumption.

#### Application

Suitable for use in passenger cars and light commercial vehicles.

#### Benefits

##### OXIDATION RESISTANCE

High thermal and oxidation stability

##### ENGINE CLEANLINESS

The optimum level of sulfate ash provides a low level of deposits in the engine

The product name in an order: Motor oil LUKOIL STANDARD SAE 15W-40, API SF/CC, STO 00044434-002-2005

#### Typical test data

The information given in the typical data does not constitute a specification and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO «LLK-International»

Property	Test methods	Value
Density at 15 °C, kg/m <sup>3</sup>	ASTM D1298 / ASTM D4052	881
Kinematic viscosity at 100 °C, mm <sup>2</sup> /s	ASTM D445	13.5
Kinematic viscosity at 40 °C, mm <sup>2</sup> /s	ASTM D445	99
Viscosity index	ASTM D2270	138
Cold Cranking Viscosity at -20°C, CCS, mPa·s	ASTM D5293 / GOST R 52559	5,285
Pumping Viscosity at -25°C (MRV), mPa·s	ASTM D4684 / GOST R 52257	22,183
Total Base Number, mg KOH/1 g oil	ASTM D2896	6.1
Sulphated ash, %	ASTM D874	0.9
Noack evaporation loss, %	ASTM D5800 / DIN 51581-1	10
Flash Point, COC, °C	ASTM D92	228
Pour Point, °C	GOST 20287 B	-32