

LUKOIL TRANSMISSION TM-3 SAE 140

MEETS REQUIREMENTS

API GL-3

TM-3-34 GOST 17479.2-85

PRODUCT DESCRIPTION

LUKOIL TRANSMISSION TM-3 SAE 140 is transmission oil formulated on highly stable mineral base and modern additive package which improves extreme pressure (EP), anti-wear, antioxidant, antifoaming and low temperature properties.

APPLICATION

Intended for use in mechanical gear boxes of commercial vehicles and other gear units of mobile machinery where API GL-3 or GOST 14779.2-85 TM-3 grade oils are recommended. The oil is designed for highly loaded transmissions working under high temperatures.

The oil is recommended for use in hot climate – where ambient temperature exceeds +30 °C. The product is also suitable for worn gears and transfer boxes which require SAE 90 and API GL-3 (TM-3) grade oils thereby performing sealing function and protecting the details from progressive wear.

FEATURES AND BENEFITS

- Reliable protection of transmission units from wear under high temperature
- Stable properties of the oil during extended operation
- Absence of viscosity modifier allows to save stable viscosity over the whole drain interval
- Excellent price-quality ratio

The product name in an order:

Oil LUKOIL TRANSMISSION TM-3 SAE 140, STO 79345251-082-2015

TYPICAL TEST DATA

PROPERTY	Test methods	LUKOIL TRANSMISSION TM-3 SAE 140
Kinematic viscosity at 100 °C, mm ² /s	GOST 33 / ASTM D445 / GOST R 53708	30
Viscosity index	GOST 25371 / ASTM D2270	91
Flash Point, COC, °C	GOST 4333 / ASTM D92	262
Pour Point, °C	GOST 20287 B	-11

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO "LLK-International".