

LUKOIL TRANSMISSION TM-5 SAE 85W-140

Extra high performance API GL-5 for heavy duty transmissions of mobile equipments

APPROVALS

ZF TE-ML 05A, 12E, 16D, 21A (ZF001603)

MEETS REQUIREMENTS

API GL-5
MIL-L-2105D
DAF, RENAULT (GL-5)

PRODUCT DESCRIPTION

LUKOIL TRANSMISSION TM-5 SAE 85W-140, API GL-5 is high-effective mineral gear oil, for mechanical transmission with cylindrical, spiral bevel and hypoid gears of passenger cars, trucks and other mobile equipment, where oil API GL-5 level is required.

LUKOIL TRANSMISSION TM-5 SAE 85W-140, API GL-5 is manufactured using specifically selected high quality mineral base stocks and a high-performance additive package of foreign manufacture.

APPLICATION

LUKOIL TRANSMISSION TM-5 SAE 85W-140, API GL-5 is recommended for heavy duty axles, final drives of passenger cars, trucks and offroad machinery (including construction, mining, agricultural machinery).

BENEFITS

- Excellent antiwear and anticorrosion properties
- Provides extended and reliable exploitation in terms of high loads
- High oxidation stability
- Excellent resistance to corrosion and foam suppression
- High lubrication performance at low temperatures

The product name in an order:

Oil LUKOIL TRANSMISSION TM-5 SAE 85W-140, API GL-5, STO 00044434-009-2006

TYPICAL TEST DATA

PROPERTY	Test methods	LUKOIL TRANSMISSION TM-5 SAE 85W-140, API GL-5
Density at 20 °C, kg/m ³	ASTM D4052	906.9
Kinematic viscosity at 100 °C, mm ² /s	GOST 33	26.3
Brookfield viscosity at -12 °C, mPa·s	ASTM D2983	45,635
Viscosity index	GOST 25371	96
Flash Point, COC, °C	GOST 4333	222
Pour Point, °C	GOST 20287 B	-22

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO "LLK-International".