

LUKOIL ATF SYNTH

Fully synthetic high-performance ATF

Approvals

- RBAS Lubricant Class TE-ML 09X
- ZF TE-ML 04D/14B
- VOITH H55.6336.xx
- MB-Approval 236.8
- MAN 339 Typ L1/V2/Z2

Meets requirements

- GM Dexron IIE
- ZF TE-ML 11A/21L
- VOLVO 97335
- Allison C-4
- Ford Mercon

Product description

Fully synthetic high-performance automatic transmission fluid for modern vehicles. Can be used in a wide temperature range. Highest shear stability, extremely high oxidation stability, effective corrosion protection, lowest possible foaming characteristics, excellent viscosity-temperature behavior and extremely low pour point allows easy gear-shifting even at very low temperatures.

Application

It is used as a power transmission fluid in automatic gearboxes of passenger cars, busses, torque converters, power steerings, hydraulic clutches, hydraulic systems (deterging multigrade hydraulic oil ISO VG 32) and as gear oil referring to manufacturer's manuals. Can be used in all automatic gearboxes which require Dexron® or Mercon® performance.

Typical test data

The information given in the typical data does not constitute a specification and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO «LLK-International»

Property	Test methods	Value
Density at 15 °C, kg/m ³	DIN 51575	840
Flash Point, COC, °C	ISO 2592	260
Kinematic viscosity at 40 °C, mm ² /s	DIN 51562/T1	34
Kinematic viscosity at 100 °C, mm ² /s	DIN 51562/T1	7.2
Viscosity index	ISO 2909	183
Pour Point, °C	ISO 3016	< -48