

LUKOIL GENESIS SPECIAL VL 0W-20

Fully synthetic engine oil for VOLVO automobiles

APPROVALS

VOLVO VCC-RBS0-2AE

PRODUCT DESCRIPTION

LUKOIL GENESIS SPECIAL VL 0W-20 is a multi-grade fully synthetic engine oil of the last generation with high fuel economy and excellent low-temperature properties

APPLICATION

Recommended for the newest 4-stroke gasoline and diesel engines of VOLVO passenger cars, operated in severe conditions when VOLVO VCC RBS0-2AE is required.

Important(!): Does not intended for use in 5 and 6-stroke VOLVO engines — for such kind of engines LUKOIL GENESIS SPECIAL A5/B5 0W-30 is recommended.

MEETS REQUIREMENTS

ACEA A1/B1

FEATURES AND BENEFITS

- Specially developed for the newest VOLVO engines
- High fuel efficiency and reduction of emissions
- Excellent low-temperature properties
- Increased protection against wear in severe conditions (cold climate, short distances)
- Geared to city Start-Stop cycle
- Prevents formation of high- and lowtemperature deposits
- Extends catalyst life due to low content of Phosphorus and sulphated ash

The product name in an order:

Motor oil LUKOIL GENESIS SPECIAL VL 0W-20, STO 79345251-074-2015

Tel.: (495) 627-40-20

Fax: (495) 981-76-84

TYPICAL TEST DATA

PROPERTY	Test methods	LUKOIL GENESIS SPECIAL VL 0W-20
Density at 20 °C, kg/m ³	ASTM D4052 / GOST 3900	840.7
Kinematic viscosity at 100 °C, mm ² /s	ASTM D445 / GOST 33 / GOST R 53708	9.16
Viscosity index	ASTM D2270 / GOST 25371	177
Cold Cranking Viscosity (CCS) at -35 °C, mPa·s	ASTM D5293 / GOST R 52559	5,750
Borderline Pumping Viscosity (MRV) at -40 °C, mPa·s	ASTM D4684 / GOST R 52257	25,300
Total Base Number, mg KOH/1 g oil	ASTM D2896 / GOST 30050	7.6
Sulphated ash, %	ASTM D874 / GOST 12417	0.856
Noack evaporation loss, %	ASTM D5800 / DIN 51581-1	12.4
Flash Point, COC, °C	ASTM D92 / GOST 4333	229
Pour Point, °C	GOST 20287 B / ASTM D97	-52

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO "LLK-International".

Otiel CIMAG