

## LUKOIL LUXE SYNTHETIC 5W-30

### Fully synthetic engine oil

#### Meets requirements

- API SL/CF
- Ford WSS-M2C-913-A/B/C/D
- IVECO 18-1811 Classe S1
- PJSC «AVTOVAZ»
- ACEA A1/B1, A5/B5
- Renault RN 0700
- Fiat 9.55535-G1

#### Product description

Fully synthetic engine oil for modern gasoline and diesel engines of passenger cars. Formulated with high-quality synthetic base oils in combination with advanced additives technology.

#### Application

Recommended for all-season use in gasoline and diesel engines (without Diesel Particulate Filters) required engine oil with API SL and/or ACEA A1/B1, A5/B5 performance level and SAE 5W-30 viscosity.

#### Benefits

##### MAXIMUM PROTECTION

Provides excellent protection against wear in severe operating conditions

##### EXCELLENT CLEANLINESS

Prevents the formation of high and low temperature deposits on engine components

##### DEPOSITS PROTECTION

Keeps valves and pistons clean and protects the catalytic converter

The product name in an order: Multigrade Engine Oil LUKOIL LUXE Synthetic SAE 5W-30, API SL/CF, STO 00044434-003-2005

#### Typical test data

The information given in the typical data does not constitute a specification and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO «LLK-International»

Property	Test methods	Value
Density at 20 °C, kg/m <sup>3</sup>	ASTM D1298 / ASTM D4052	850
Kinematic viscosity at 100 °C, mm <sup>2</sup> /s	ASTM D445	10.6
Kinematic viscosity at 40 °C, mm <sup>2</sup> /s	ASTM D445	60.9
Viscosity index	ASTM D2270	165
Dynamic viscosity (CCS) at -30°C, mPa·s	ASTM D5293 / GOST R 52559	4,941
Dynamic viscosity (MRV) at -35°C, mPa·s	ASTM D4684 / GOST R 52257	20,100
Total Base Number, mg KOH/1 g oil	ASTM D2896	10.9
Sulphated ash, %	ASTM D874	1.2
Noack evaporation loss, %	ASTM D5800 / DIN 51581-1	9.6
Flash Point, COC, °C	ASTM D92	235
Pour Point, °C	GOST 20287 B	-46