

LUKOIL GENESIS SPECIAL A3/B4 5W-40

Fully synthetic motor oil

Approvals

- API SN
- MB-Approval 226.5/229.5
- Renault RN 0700/0710
- VW 502 00/505 00

Meets requirements

- ACEA A3/B3, A3/B4
- Fiat 9.55535-N2/Z2
- PSA B71 2296
- API CF

Product description

Synthetic engine oil formulated with high quality synthetic base oils and advanced additive technology. Recommended for car maintenance at service stations.

Application

Recommended for use in gasoline and diesel engines of Renault, Mercedes-Benz cars, as well as cars of the VAG concern. The oil can also be used in engines requiring the use of API SN or ACEA A3/B4 oil in combination with a viscosity of 5W-40.

Benefits

EXCELLENT CLEANLINESS

Prevents the formation of high and low temperature deposits on engine components

MAXIMUM PROTECTION

Provides excellent protection against wear in severe operating conditions

The product name in an order: Motor Oil LUKOIL GENESIS SPECIAL A3/B4 5W-40, STO 79345251-074-2015

Typical test data

The information given in the typical data does not constitute a specification and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO «LLK-International»

Property	Test methods	Value
Density at 15 °C, kg/m ³	ASTM D1298 / ASTM D4052	845
Kinematic viscosity at 100 °C, mm ² /s	ASTM D445	13.2
Viscosity index	ASTM D2270	180
Dynamic viscosity (CCS) at -30°C, mPa·s	ASTM D5293 / GOST R 52559	5,248
Dynamic viscosity (MRV) at -35°C, mPa·s	ASTM D4684 / GOST R 52257	23,300
Total Base Number, mg KOH/1 g oil	ASTM D2896	10.5
Sulphated ash, %	ASTM D874	1.2
Noack evaporation loss, %	ASTM D5800 / DIN 51581-1	9.7
Flash Point, COC, °C	ASTM D92	222
Pour Point, °C	GOST 20287 B	-40