

LUKOIL THERMOFLEX EP 3-180

Multipurpose high-temperature complex lithium grease

DESCRIPTION

LUKOIL® THERMOFLEX EP 3-180 is a multipurpose high-temperature grease based on complex lithium soap, highly refined mineral oils blend with low evaporation, good stability to oxidation. The grease contains high-performance additive package.

LUKOIL® THERMOFLEX EP 3-180 has excellent tribological features and can operate under heavy mechanical loads and in frequent contact with water. Service temperature range is from –30 °C up to +160 °C.



ADVANTAGES:

- High extreme pressure (EP) properties
- Superior sealing effect
- Excellent adhesion
- Long-term service life
- Great water resistance
- Good anti-corrosion properties
- Resistance to shock and vibrational loads

COMPOSITION:

- Highly refined mineral oils
- Complex lithium soap
- Additives package: anti-wear and extreme pressure (AW/EP), anti-corrosion, anti-oxidation

APPLICATION IN UNITS:

- Rolling and sliding bearings operating for a long time while on high speeds and under heavy loads, exposed to intensive vibrations and at high temperatures
- Guideways
- Bushings, swivels, units where sealing effect of the lubricant is required to prevent dirt, dust, water and steam from getting inside

APPLICATION EXAMPLES:

- Wheel bearings of passenger and commercial vehicles
- Bearings of industrial fans, electric motors, couplings, shafts, pumps and other industrial equipment
- Used as multipurpose lubricant in automotive machinery, agricultural, mining, and construction equipment
- Vertically mounted bearings

LUKOIL® THERMOFLEX EP 3-180. Edition 12/21 replaces edition 04/18

This product is manufactured according to STO 65561488-013-2014

LUKOIL® THERMOFLEX EP 3-180 TYPICAL PROPERTIES

Standard	Property	Unit	Value
DIN 51502	Marking according to DIN 51502		KP3P-30
ISO 6743-9	Marking according to ISO 6743-9		L-XCEHB 3
	Color		Blue to dark blue
	Service temperature range	°C	–30 to +160
DIN 51818	NLGI grade		3
ISO 2137	Worked penetration (60 strokes)	mm/10	220–250
ISO 2137	Penetration change @ 25 °C after 10000 cycles	mm/10	±10
DIN 51562	Base oil viscosity @ 40 °C	mm²/s	180
DIN 51562	Base oil viscosity @ 100 °C	mm²/s	16
ISO 2176	Dropping point	°C	>260
ASTM D2596	Four Ball Weld Load @ 25°C	N	3283
		kg	335
ASTM D2266	Four Ball Wear Scar Diameter	mm	0.5
DIN 51802	Corrosion protection (SKF-Emcor, distilled water)		0-0
ASTM D4048	Copper corrosion		1a

HOW TO USE

This grease can be applied manually with a brush or spatula.

USABLE LIFE AND STORAGE

The guaranteed shelf life is 36 months from the date of manufacture in the manufacturer's container, subject to the conditions of transportation and storage.

HANDLING PRECAUTIONS

This product doesn't contain any toxic ingredients. During storage, transportation, and application of this product, the safety rules for handling mineral lubricating materials and the environment protection regulations must be observed.

For further information on how to use LUKOIL® products, please refer to the product MSDS.

TECHNICAL SUPPORT

For correct selection of the proper lubricating materials to meet your needs, and to get more detailed information on the products, as well as if you have any other questions, we recommend you to contact our technical support service specialists by e-mail: grease.support@lukoil.com

LUKOIL® THERMOFLEX EP 3-180. Edition 12/21 replaces edition 04/18

Product technical properties are typical and can vary in strong limits.

Due to research and development of science and technology technical properties of product indicated in this Technical Data Sheet can be changed without notification.