

## LUKOIL STABIO 460

### High quality compressor oil

#### Meets requirements

- DIN 51506 (VBL)

#### Product description

High quality mineral compressor oil designed to meet the latest requirements to lubricants for modern high power air compressors used for severe operation. Highly refined base stocks and effective additive package ensuring good protection against oxidation, sludge formation, wear and foaming and possesses good seals compatibility.

#### Application

Designed for use in piston type compressors. The oil can also be used in circulation systems for lubrication of plain and rolling bearings at high operation temperatures.

The product name in an order: Compressor oil LUKOIL STABIO 460, STO 79345251-018-2009

#### Typical test data

The information given in the typical data does not constitute a specification and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO «LLK-International»

Property	Test methods	Value
Density at 20 °C, kg/m <sup>3</sup>	ASTM D1298 / ASTM D4052	896
Kinematic viscosity at 40 °C, mm <sup>2</sup> /s	ASTM D445	470
Kinematic viscosity at 100 °C, mm <sup>2</sup> /s	ASTM D445	29.9
Flash Point, COC, °C	ASTM D92	305
Pour Point, °C	GOST 20287 B	<-10
Tribological properties on four-ball machine: -Wear scar diameter, mm	GOST 9490	0.32