

LUKOIL DOT 4 CLASS 6

High quality brake and clutch fluid DOT 4 CLASS 6

Meets requirements

- SAE J 1703, J 1704
- FMVSS 116 DOT 4
- ISO 4925 CLASS 6

Product description

High performance fluid with improved properties designed for brakes and clutches of modern vehicles equipped with electronic brake systems. The brake fluid doesn't have a negative effect on the parts of the brake system and has high thermal oxidation stability. LUKOIL DOT 4 CLASS 6 is compatible with the following brake fluids: DOT 3, DOT 4. The brake fluid has high thermal oxidation stability, excellent protection to the brake system components and low kinematic viscosity. To ensure maximum efficiency and maintain high quality characteristics, a complete replacement of the brake fluid should be performed.

Application

Specially developed for hydraulic brake systems and clutches of cars which are manufactured in Russia and abroad. Intended for use in cars equipped with: Anti-lock braking system (ABS); Electronic stability program (ESP); Traction Control System (TCS); Active Stability Control (ASC).

The product name in an order: Brake fluid LUKOIL DOT 4 CLASS 6, STO 82851503-048-2013

Typical test data

The information given in the typical data does not constitute a specification and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO «LLK-International»

Property	Test methods	Value
Kinematic viscosity at 100 °C, mm ² /s	ASTM D445	1.71
Kinematic viscosity at -40 °C, mm ² /s	ASTM D445 / GOST 33 / GOST R 53708	750
Boiling temperature of dry fluid, °C	p.11.3	263
Boiling temperature of wet fluid, °C	p.11.4	172
pH at 20 °C	GOST 22567.5	9.67