

LUKOIL GENESIS SPECIAL A5X 5W-30

Fully synthetic engine oil for reduced fuel consumption

Approvals

- API SL

Meets requirements

- ACEA A5/B5
- Jaguar Land Rover ST JLR.03.5003
- IVECO 18-1811 Classe S1
- API CF
- Ford WSS-M2C-913-A/B/C/D
- Fiat 9.55535-G1
- Renault RN 0700
- Отвечает требованиям моторных тестов спецификации API SN

Product description

Synthetic engine oil developed for modern gasoline and diesel engines (without DPF) of Korean OEM such as Kia and Hyundai. Well balanced formulation exceeds OEM requirements and guarantee reliable engine protection performance even in urban cycle conditions.

Application

Designed for Kia/Hyundai cars, but also can be used for service after warranty cars such as Toyota, Lexus, Ford, Jaguar, Land Rover, Volvo и Renault (only gasoline engines where RN 0700 is required). The oil can be used in diesel engines with a particulate filter, for which the manufacturer specifies Ford WSS-M2C-913-C or D.

Benefits

MAXIMUM PROTECTION

Adjusted for severe conditions of urban cycle

EASY COLD START

Excellent low-temperature properties

FUEL ECONOMY

Superior fuel economy thanks to lower HTHS viscosity and potential to reduce emissions

The product name in an order: Motor oil LUKOIL GENESIS SPECIAL A5X 5W-30, STO 79345251-074-2015

Typical test data

The information given in the typical data does not constitute a specification and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO «LLK-International»

Property	Test methods	Value
Density at 15 °C, kg/m ³	ASTM D1298 / ASTM D4052	845
Kinematic viscosity at 100 °C, mm ² /s	ASTM D445	10.1
Viscosity index	ASTM D2270	176
Dynamic viscosity (CCS) at -30°C, mPa·s	ASTM D5293 / GOST R 52559	3,416
Dynamic viscosity (MRV) at -35°C, mPa·s	ASTM D4684 / GOST R 52257	13,193
Total Base Number, mg KOH/1 g oil	ASTM D2896	11.1
Sulphated ash, %	ASTM D874	1.1
Noack evaporation loss, %	ASTM D5800 / DIN 51581-1	11
Flash Point, COC, °C	ASTM D92	223
Pour Point, °C	GOST 20287 B	-40